

Fittings For Chain Cable

Manufacturer **Jiangsu Asian Star Anchor Chain Co. Ltd**

Address Hede Village, Dongxing Town, Jingjiang, 214500, China

Type Fittings For Chain Cable

This approval is subject to compliance with the Rules for the Manufacture, Testing and Certification of Materials. The full details of the processes and grades to which this approval applies are given on subsequent pages of this certificate.

This certificate is issued to the named manufacturer, and is valid until the expiry date specified. Lloyd's Register is to be notified of any change that may affect the validity of this certificate, and reserves the right to cancel or withdraw this certificate.

Approval Notes Grades U2 approved for the normalized supply condition and grade U3 approved for the quenched and tempered supply condition.

Blooms for R3, R3S, R4 and R4S fittings supplied by Jiangying Xingcheng Special Steel Works Co., Ltd.

Billet for R5 fittings supplied by Baoshan Iron & Steel Co., Ltd.

Approved for the forging, heat treatment and proof load testing of fittings.



71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Gavin Young

Senior Metallurgist to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Fittings For Chain Cable

Fittings for Chain Cable	Forged Fittings	Grades	Maximum Diameter	Units
-	-	R5	137.00	mm
Fittings for Chain Cable	Forged Fittings	Grades	Nominal Maximum Diameter	Units
-	-	R3	187.00	mm
-	-	R3S	187.00	mm
-	-	R4	187.00	mm
-	-	R4S	187.00	mm
-	-	U2	122.00	mm
-	-	U3	122.00	mm



71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.